ezH2O® Bottle Filling Station & Integral Soft Sides® Fountain Non-Filtered Non-Refrigerated Stainless

Model EZWS-EDFP217K


PRODUCT SPECIFICATIONS

ezH2O® Bottle Filling Station & Integral Soft Sides® Fountain Non-Filtered Non-Refrigerated Stainless. Features shall include Antimicrobial*, Green Ticker™, Hands Free, Laminar Flow, Real Drain. Furnished with Flexi-Guard ® Safety Bubbler. Electronic Bottle Filler Sensor with Mechanical Front Bubbler Button activation. Product shall be Wall Mount (Inwall Frame/Plate), for Indoor applications, serving 2 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120.

Special Features:	Antimicrobial, Green Ticker™, Hands		
-	Free, Laminar Flow, Real Drain		
Finish:	Stainless Steel (S)		
Power:	115V/60Hz		
Bubbler Style:	Flexi-Guard ® Safety Bubbler		
Activation by:	Electronic Bottle Filler Sensor with Mechanical Front Bubbler Button		
Mounting Type:	Wall Mount (Inwall Frame/Plate)		
Chilling Capacity:	Non-refrigerated		
Full Load Amps	1		
Rated Watts:	15		
Dimensions (L x W x H):	38-1/2" x 19-3/8" x 34-5/8"		
Approx. Shipping Weight:	118 lbs.		
Installation Location:	Indoor		
No. of Stations Served:	2		

Special Note: Non-filtered model. If rear access is not available front access panels may be required such as ACCESS12X38-5 or AP99.

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Green Ticker: Informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.
- Key plastic components are manufactured with silver ion antimicrobial agent helping to provide clean, stain- and odor-free surfaces.
- Real Drain System eliminates standing water.
- *Antimicrobial claims are in refence to components manufactured antimicrobial agents, helping to provide clean, stain- and odor-free surfaces.





Included with Product:

Fountain (EDFP217WS), Mounting Frame (MFWS200)

▼ Ships in multiple boxes.

A Century of Tradition and Quality.
For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

CAN/CSA C22.2 No. 120

GreenSpec®

NSF/ANSI 61 (Q≤1) & 372 (lead free)

UL 399









Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 2000000488 Installation Instructions (PDF) - 0000000755

Electrical components and water system are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

Warranty (PDF)



ezH2O® Bottle Filling Station & Integral Soft Sides® Fountain Non-Filtered Non-Refrigerated Stainless Model EZWS-EDFP217K

Optional Accessories		
EWF3000	Universal Filtration Kit (3000-Gallon) Spec Sheet (PDF)	
<u>97258C</u>	Cane Apron for Contour™ & Soft Sides® Models Black <u>Spec Sheet (PDF)</u>	V
ACCESS12X38-5	Stainless Steel Access Panel for Bi-Level Architectural Fountains Spec Sheet (PDF)	

ezH2O® Bottle Filling Station & Integral Soft Sides® Fountain Non-Filtered Non-Refrigerated Stainless


Model EZWS-EDFP217K

IMPORTANT! INSTALLER PLEASE NOTE:

The grounding of electrical equipment such as telephone, computers, etc., to water lines is a common procedure. This grounding may be in the building or may occur away from the building. This grounding can cause electrical feedback into a water cooler, creating an electrolysis which causes a metallic taste or causes an increase in the metal content of the water. This condition is avoidable by using the proper materials as indicated below. The drain fittings which are provided by the installer should also be plastic to electrically isolate the cooler from the building plumbing system.

OPERATION OF QUICK CONNECT FITTINGS Simply push in Tube is secured Push in collet to tube to attach release tube in position Pushing tube in before pulling it out helps to release tube 1/4" O.D. tube 3/8" O.D. Tube connect **Building** water water inlet to cold water supply inlet cooler Servicé stop NOTE: Waterflow (Not furnished) direction

BOTTLE FILLER SPECIFICATIONS



NOTE: New Installations Must Use Ground Fault Circuit Interrupter (GFCI).



ezH2O® Bottle Filling Station & Integral Soft Sides® Fountain Non-Filtered Non-Refrigerated Stainless

Model EZWS-EDFP217K

WALL OPENING

IMPORTANT: It is necessary to create a wall opening 37-1/2" W x 31-3/4" H and 25" above the floor line. ELECTRICAL DATA

Electical outlet, three (3) conductor grounded. Locate withing safe reach of power cord.

MOUNTING INSTRUCTIONS

Refer to rough-in for location of plumbing and electrical sources. The support frame is to be installed first. Hang upper panel to hanger on frame. Fountains are to be attached to panel and wall frame. Water service lines, waste lines and electrical are assembled as required. Perform a final check for leaks and correct functions of fountains and chiller. (For details see the installation instructions.)
Installation requires trap to be installed in wall. Trap and service stop not included.

MOUNTING FRAME MFWS200

INSTALLER NOTE

This drinking fountain is furnished with a bubbler and valve including all connecting fittings which are manufactured of completely lead free material. Shut off valve (not furnished) to accept 3/8" O.D. unplated copper tube.

